

## 25LET

General specifications		
Product name		Eaton Bussmann series high speed British standard fuse
Part no.		25LET
EAN		5027590470896
Product Length/Depth		55 millimetre
Product height		18 millimetre
Product width		18 millimetre
Product weight		32 gram
Compliances		CE Marked RoHS Compliant
Certifications		IEC Rated UL Recognized IEC 60269-4 Designed and tested to BS88 part 4
Product Tradename		None
Product Type		High speed British standard fuse
Product Sub Type		None
Electrical data		
Amperage Rating		25 A
Voltage rating		280 V
Rated voltage AC		280 V
Rated voltage DC		150 V
Interrupt rating		200 kA RMS Sym, 50 kA DC at 150 Vdc
Class		Class aR
Clearing (I <sub>ZT</sub> )		250
Watt losses		4 W
Product specifications		
Application		Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse indicator		None
Compatible Trip indicator/microswitch		
Suitable for		TI500 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor

## Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	280
Rated voltage DC	V	150
Rated current	A	25
Utilization category		Other
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	4
Mounting holes		M6
Centre-to-centre distance of connections	mm	41