

A



95.13.2



95.15.2

Approvals  
(according to type):





|                                                                  |                                            |                  |                     |                  |
|------------------------------------------------------------------|--------------------------------------------|------------------|---------------------|------------------|
| PCB socket                                                       | 95.13.2 (blue)                             | 95.13.20 (black) | 95.15.2 (blue)      | 95.15.20 (black) |
| For relay type                                                   | 40.31                                      |                  | 40.51, 40.52, 40.61 |                  |
| <b>Accessories</b>                                               |                                            |                  |                     |                  |
| Metal retaining clip (supplied with socket - packaging code SMA) |                                            |                  | 095.51              |                  |
| Plastic retaining clip                                           |                                            |                  | 095.52              |                  |
| <b>Technical data</b>                                            |                                            |                  |                     |                  |
| Rated values                                                     | 12 A - 250 V                               |                  | 10 A - 250 V *      |                  |
| Dielectric strength                                              | 6 kV (1.2/50 µs) between coil and contacts |                  |                     |                  |
| Protection category                                              | IP 20                                      |                  |                     |                  |
| Ambient temperature                                              | °C -40...+70                               |                  |                     |                  |



\* For currents > 10 A, contact terminals must be connected in parallel (21 with 11, 24 with 14, 22 with 12).  
With the relay 40.51 the change-over contact will be 21-12-14.



40.31




40.51




95.13.2

Copper side view




40.52



95.15.2

Copper side view



40.61

## Packaging codes

How to code and identify retaining clip and packaging options for sockets.

Example:

9 5 . 0 5 S P A

A Standard packaging

SM Metal retaining clip  
SP Plastic retaining clip

9 5 . 0 5

Without retaining clip

