

12, 16 and 19-Pin *multifast*® Field Wireable In-line Connectors

- Female Contact Holder & Thread
- For Use with Custom Wiring & Junction Boxes
- Convert Hard Wiring into Quick Disconnect
- IEC IP 65 Protection



Housing Style	Part #	Cable	Features	Pinout
	CK 12-0	Nickel plated brass PG 11 cable gland, Accepts 4-10 mm cable diameter Accepts up to 12x18 AWG conductors 125° C 300 V, 8.0 A	Field wireable 12-pin in-line connector, for use with <i>minifast</i> ®, <i>eurofast</i> ® (single input per port) and <i>microfast</i> ® junctions boxes	
	CK 16-0	Nickel plated brass PG 13.5 cable gland, Accepts 5-12 mm cable diameter Accepts up to 16x18 AWG conductors 125° C 150 V, 8.0 A	Field wireable 16-pin in-line connector, for use with <i>eurofast</i> ® (isolated power supply) junctions boxes	
	CK 19-0	Nickel plated brass PG 13.5 cable gland, Accepts 5-12 mm cable diameter Accepts up to 19x18 AWG conductors 125° C 150 V, 8.0 A	Field wireable 19-pin in-line connector, for use with <i>eurofast</i> ® (two Signals per port) junctions boxes	
	CK 125-0	Nickel plated brass IAC, Accepts 3-10 mm cable diameter Accepts up to 12x18 AWG conductors 125° C 150 V, 8.0 A	Field wireable 12-pin in-line connector	

12, 16 and 19-Pin *multifast*® Field Wireable In-line Connectors

- Male Contact Holder & Thread
- For Use with Custom Wiring & Junction Boxes
- Convert Hard Wiring into Quick Disconnect
- IEC IP 65 Protection



Housing Style	Part #	Cable	Features	Pinout
	CSS 12-0	Nickel plated brass PG 13.5 cable gland, Accepts 5-12 mm cable diameter Accepts up to 12x18 AWG conductor 125° C 300 V, 8.0 A	Field wireable 12-pin in-line connector, for use with <i>minifast</i> ®, <i>eurofast</i> ® (single input per port) and <i>microfast</i> junctions boxes	
	CSS 16-0	Nickel plated brass PG 13.5 cable gland, Accepts 5-12 mm cable diameter Accepts up to 16x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 16-pin in-line connector, for use with <i>eurofast</i> ® (isolated power supply) junctions boxes	
	CSS 19-0	Nickel plated brass PG 13.5 cable gland, Accepts 5-12 mm cable diameter Accepts up to 19x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 19-pin in-line connector, for use with <i>eurofast</i> ® (two signals per port) junctions boxes	
	CSS 125-0	Nickel plated brass IAC, Accepts 3-10 mm cable diameter Accepts up to 12x18 AWG conductors 125° C 150 V, 8.0 A	Field wireable 12-pin in-line connector	

12, 16 and 19-Pin multifast® Field Wireable In-line Connectors

- Male Contact Holder, Female Thread
- For Use with Custom Wiring & Junction Boxes
- Convert Hard Wiring into Quick Disconnect



Housing Style	Part #	Cable	Features	
	CS 12-0	Nickel plated brass PG 11 cable gland, Accepts 4-10 mm cable diameter Accepts up to 12x18 AWG conductor 125° C 300 V, 8.0 A	Field wireable 12-pin in-line connector, for use with minifast®, eurofast® (single input per port) and microfast® junctions boxes	
	CS 16-0	Nickel plated brass PG 13.5 cable gland, Accepts 5-12 mm cable diameter Accepts up to 16x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 16-pin in-line connector, for use with eurofast® (isolated power supply) junctions boxes	
	CS 19-0	Nickel plated brass PG 13.5 cable gland, Accepts 5-12 mm cable diameter Accepts up to 19x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 19-pin in-line connector, for use with eurofast® (two Signals per port) junctions boxes	
	CS 125-0	Nickel plated brass IAC, Accepts 3-10 mm cable diameter Accepts up to 12x18 AWG conductors 125° C 150 V, 8.0 A	Field wireable 12-pin in-line connector	

12, 16 and 19-Pin *multifast*® Field Wireable, Front Mount

- Female and Male Connectors
- For Use with Custom Wiring & Junction Boxes
- Convert Hard Wiring into Quick Disconnect
- IEC IP 65 Protection



Housing Style	Part #	Cable	Features	Pinout
	CKF 12-0	Nickel plated brass Accepts up to 12x18 AWG conductor 125° C 300 V, 8.0 A	Field wireable 12-pin receptacle, for use with <i>minifast</i> ®, <i>eurofast</i> ® (single input per port) and <i>microfast</i> ® junctions boxes	
	CKF 16-0	Nickel plated brass Accepts up to 16x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 16-pin receptacle, for use with <i>eurofast</i> (isolated power supply) junctions boxes	
	CKF 19-0	Nickel plated brass Accepts up to 19x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 19-pin receptacle, for use with <i>eurofast</i> (two signals per port) junctions boxes	
	CSF 12-0	Nickel plated brass Accepts up to 12x18 AWG conductor 125° C 300 V, 8.0 A	Field wireable 12-pin receptacle, for use with <i>minifast</i> ®, <i>eurofast</i> ® (single input per port) and <i>microfast</i> ® junctions boxes	
	CSF 16-0	Nickel plated brass Accepts up to 16x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 16-pin receptacle, for use with <i>eurofast</i> (isolated power supply) junctions boxes	
	CSF 19-0	Nickel plated brass Accepts up to 19x18 AWG conductor 125° C 150 V 8.0 A	Field wireable 19-pin receptacle, for use with <i>eurofast</i> (two signals per port) junctions boxes	

12, 16 and 19-Pin *multifast*® Field Wireable Receptacles, Front Mount, Long Threads

- Female and Male Connectors
- For Use with Custom Wiring & Junction Boxes
- Convert Hard Wiring into Quick Disconnect
- IEC IP 65 Protection



Housing Style	Part Number	Cable	Features	
	CKFL 12-0	Nickel plated brass Accepts up to 12x18 AWG conductor 125° C 300 V, 8.0 A	Field wireable 12-pin receptacle, for use with <i>minifast</i> ®, <i>eurofast</i> ® (single input per port) and <i>microfast</i> ® junctions boxes	
	CKFL 16-0	Nickel plated brass Accepts up to 16x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 16-pin receptacle, for use with <i>eurofast</i> (isolated power supply) junctions boxes	
	CKFL 19-0	Nickel plated brass Accepts up to 19x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 19-pin receptacle, for use with <i>eurofast</i> (two signals per port) junctions boxes	
	CSFL 12-0	Nickel plated brass Accepts up to 12x18 AWG conductor 125° C 300 V, 8.0 A	Field wireable 12-pin receptacle, for use with <i>minifast</i> ®, <i>eurofast</i> ® (single input per port) and <i>microfast</i> ® junctions boxes	
	CSFL 16-0	Nickel plated brass Accepts up to 16x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 16-pin receptacle, for use with <i>eurofast</i> (isolated power supply) junctions boxes	
	CSFL 19-0	Nickel plated brass Accepts up to 19x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 19-pin receptacle, for use with <i>eurofast</i> (two Signals per port) junctions boxes	

12, 16 and 19-Pin *multifast*® Field Wireable Receptacles, Rear Mount

- Female Contact Holder & Thread
- For Use with Custom Wiring & Junction Boxes
- Convert Hard Wiring into Quick Disconnect
- IEC IP 65 Protection



Housing Style	Part Number	Cable	Features	Pinout
	CKFD 12-0	Nickel plated brass Accepts up to 12x18 AWG conductor 125° C 300 V, 8.0 A	Field wireable 12-pin receptacle, for use with <i>minifast</i> ®, <i>eurofast</i> ® (single input per port) and <i>microfast</i> junctions boxes	
	CKFD 16-0	Nickel plated brass Accepts up to 16x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 16-pin receptacle, for use with <i>eurofast</i> (isolated power supply) junctions boxes	
	CKFD 19-0	Nickel plated brass Accepts up to 19x18 AWG conductor 125° C 150 V, 8.0 A	Field wireable 19-pin receptacle, for use with <i>eurofast</i> (two signals per port) junctions boxes	