

V&A® Test instrument
[中文版](#)
[HOME](#)
[ABOUT V&A](#)
[TRADE SHOW](#)
[SERVICE](#)
[CONTACT US](#)
[SITE MAP](#)

SHANGHAI YIHUA V&A INSTRUMENT CO., LTD.

Professional test instrument

Products
[Infrared thermometer](#)
[Digital multimeter](#)
[Clamp meter](#)
[Cable tester / Line tracker](#)
[Professional test instrument](#)
[Analogue multimeter](#)
[DC Power supply](#)
[Accessory](#)

Professional test instrument

- [VA6450](#)
- [MS6610](#)
- [MS6500 / MS6501](#)
- [MS5710 >](#)
- [MS5209](#)


CATALOGUE REQUEST

MS5710 PHASE DETECTOR/EARTH RESISTANCE TESTER


PHASE DETECTOR

- Voltage range: 110V ~ 480V
- Test time: 110V: continuance 220V: 30 minutes 480V: 4 minutes
- Frequency response: 40 ~ 70Hz
- Inclination variation: $\pm 15^\circ$ / horizontal Operation temperature and humidity: T: $0^\circ\text{C} \sim 40^\circ\text{C}$ ($32^\circ\text{F} \sim 104^\circ\text{F}$), H: $\leq 70\%$ (non-condensating)
- Storage temperature and humidity: T: $-10^\circ\text{C} \sim 50^\circ\text{C}$ ($14^\circ\text{F} \sim 122^\circ\text{F}$), H: $\leq 70\%$ (non-condensating)
- Dielectric strength: 2000VAC for 1 minute (between circuit and product, at 50/60Hz)
- Insulation resistance: $\geq 100\text{M}\Omega$ (between circuit and product)
- Clip leads length: 1.2m
- Size: 70x95x55mm
- Weight: 280g
- Accessories: carrying case, instruction manual, fuse (FF0.5A/700V)

[| HOME](#) | [ABOUT V&A](#) | [PRODUCTS](#) | [NEW PRODUCTS](#) | [SERVICE](#) | [TRADE SHOW](#) | [CONTACT US](#) | [SITE MAP](#) |

Copyright 2005 SHANGHAI YIHUA V&A INSTRUMENT CO.,LTD. All Rights Reserved