

TIPO SR3P-611 MENIS

PL

(Unit: mm)

Dimensions	Terminal Arrangement/ Internal Connections	Mounting hole and PCB dimensions (bottom view)
PL08 		Two, 3.5 dia. or M3 device mounting holes Two, 3.5 or M3 Socket mounting holes $L = 40 \text{ mm}$ MK2(Z)P $L = 74 \text{ mm}$ PU, AMD-S, MM2(X)P, CZ, STP, H3L, TDS, DTS, DSP, TDF, TDV $L = 86 \text{ mm}$ 61F-GP/APN, G4Q-212S, RD2P, RDA, TDA, AGF, SE, SAD, K2CU, SOV-F
PL08-Q 	 (Bottom View)	Two 3.5-dia. or two M3 Socket mounting holes $L = 40 \text{ mm}$ MK2(Z)P
PLE08-0 		Two 3.5-dia. Hold-down Clip mounting holes $L = 40 \text{ mm}$ MK2(Z)P
PL11 		Two, 3.5 dia. or M3 device mounting / Hold-down Clip mounting holes Two, 3.5 dia. or M3 Socket mounting holes $L = 40 \text{ mm}$ MK3P MK2KP $L = 74 \text{ mm}$ MM3P MK2(X)KP
PL11-Q 	 (Bottom View)	Two, 3.5-dia. or M3 Socket mounting holes $L = 42 \text{ mm}$ MK3ZP MK3LP
PLE11-0 		Two, 3.5-dia. holes / Applicable model / Hold-down Clip mounting holes $L = 40 \text{ mm}$ MK3P MK2KP $L = 42 \text{ mm}$ MK3ZP MK3LP